

NOTES:

- 1. SCREENS ARE PRESENT ON ALL RAIN TANK INLETS TO REMOVE DEBRIS AND LARGER PARTICLES AS THE WATER ENTERS THE TANK. REMOVABLE CHILD-RESISTANT COVERS AND MOSQUITO SCREENING ARE IN PLACE.
- 2. TANK IS CHILD SAFE: ACCESS IS CHILD-PROFF AND THE BARREL IS PROPERLY SITED AND ANCHORED ON A STABLE SURFACE TO PREVENT TANK FROM TIPPING OVER.
- 3. ABOVE-GROUND TANKS SHALL NOT LOCATED ON UNEVEN OR SLOPED SURFACE; IF INSTALLED ON A SLOPED SURFACE, THE BASE WHERE THE TANK IS INSTALLED HAS BEEN LEVELED USING APPROPRIATE CONSTRUCTION MATERIAL PRIOR TO INSTALLATION.
- 4. INSTALLED RAIN TANKS SHALL NOT BEEN PLACED ON ELEVATED PLATFORMS, DECKS OR PORCHES WITHOUT CONSULTING LOCAL BUILDING CODE OFFICIALS.
- 5. DIRECT OVERFLOW DISCHARGE PER BUREAU OF ENGINEERING AND BUILDING AND SAFETY REQUIREMENTS.
- 6. DISPERSION IS DIRECTED SO AS NOT TO KNOWINGLY CAUSE GEOTECHNICAL HAZARDS RELATED TO SLOPE STABILITY OR TRIGGERING EXPANSIVE (CLAYEY) SOIL MOVEMENT.
- 7. RAIN TANKS SHALL BE OPAQUE AND DARK IN COLOR TO PREVENT UV LIGHT PENETRATION AND DISCOURAGE ALGAE GROWTH.
- 8. TANK PLACEMENT SHALL ALLOW EASY ACCESS FOR REGULAR MAINTENANCE.
- 9. COLLAPSIBLE RAIN TANKS ARE NOT PERMITTED.
- 10. SEE RAIN TANK FACT SHEETS FOR MORE INFORMATION.

RAIN TANKS WITH SHADE TREE PLANTING:

- TRESS MUST BE PLANTED AT LEAST 10 FEET FROM THE HOUSE FOUNDATION AND ATLEAST 5 FEET FROM FENCES, PATIOS, DRIVEWAYS AND SIDEWALKS.
- TREES SHOULD NOT BE PLANTED IN AREAS WHERE PERMEABLE PAVEMENT, POROUS CONCRETE OR PERMEABLE PAVERS ARE INSTALLED.

A LIST OF SHADE TREES CAN BE FOUND AT: WWW.CITYPLANTS.ORG